

# 3300FWBL800AS

## Support

Closed cell polyethylene (PE) foam  
White

## Adhesive

Solvent acrylic

## Liner

Filmic  
Light blue

## Characteristics

Permanent double-sided tape, good cohesion and UV resistance. Suitable for application indoors and outdoors. The PE liner is easy to peel off without being torn. [Version with light blue filmic liner]

## Recommended for

HSE plastics • Crude metal • Polyester-coated metals • Glass • Mirrors

## Industries

Plastic Material • Furniture & Furnishing • Building & Construction • Household appliances • Electronics • Automotive  
• Silk screen printing

## Applications

Plastic trims • Thermoform assembly (Caravans) in polystyrene (PST) • Fastening mirrors • Fastening frames • Fastening fridge components • Printed circuit production • Fastening emblems • Mouldings • Fastening inner vehicle panels • Fastening enamelled plates • Fastening anodised plates

Formats (mm. x Mt)	Unit of Measurement	Carrier + adhesive thickness (my)	Peel Adhesion (N/25mm)	Min. working temperature (°C)	Max. working temperature (°C)
1220x50	m <sup>2</sup>	800	17	- 30	+ 100

## TEST METHODS

International standards (FINAT, AFERA, PSTC, ASTM, TLMI, ISO).

## SAFETY INFORMATION

This product is not classified as dangerous for the environment or human health and it complies with current regulations such as the REACH Regulation and the RoHS Directive.

## USE AND STORAGE

The functionality and efficiency of the adhesive material is guaranteed 12 months from the date of delivery. We recommend to store it respecting the following indications:

- Environmental Temperature from + 15 ° C to + 22 ° C
- Humidity less than 65%
- Avoid exposing the material to direct light and sources of heat
- Store the material in the original packaging and remove the packaging only before use

Before applying the adhesive tape, the surface must be clean and dry.

In case of particular processing it is advisable to evaluate the suitability of the product by means of a preliminary test.

Our technical staff is available for any support.

Prades Srl will not be responsible for any direct, indirect or incidental loss or damage resulting from incorrect use of the product. Therefore, the user assumes all risk and liability due to improper use of this article.

## NOTE

The technical data shown in this sheet have been obtained from Prades Srl directly from the documentation provided by the manufacturer.

This data may be subject to change without prior notice.



PRADES SRL  
Via 1° Maggio, 9  
35035 Mestrino (PD) - ITALY



+39 049 9002797



web@prades.it



www.prades.it

Certificati ISO 9001



ISO 9001