900158

Support
Polyester (PET)
Clear

Adhesive
Rubber solvent base

Liner
Filmic
White

Characteristics
Permanent/removable double-sided tape. Available in spools with extended liner for easy removal.

Recommended for
Polyethylene (PE) • Polypropylene (PPL)

Industries
Plastic Material

Applications
Closing bags (open-close)

Formats (mm x Mt)	Unit of Measurement	Carrier + adhesive thickness (my)	Peel Adhesion (N/25mm)	Min. working temperature (°C)	Max. working temperature (°C)
8/18x5000	RT	53	8/12	- 20	+ 120

TEST METHODS
International standards (FINAT, AFERA, PSTC, ASTM, TLMI, ISO).

SAFETY INFORMATION
This product is not classified as dangerous for the environment or human health and it complies with current regulations such as the REACH Regulation and the RoHS Directive.

USE AND STORAGE
The functionality and efficiency of the adhesive material is guaranteed 12 months from the date of delivery. We recommend to store it respecting the following indications:
- Environmental Temperature from + 15 ° C to + 22 ° C
- Humidity less than 65%
- Avoid exposing the material to direct light and sources of heat
- Store the material in the original packaging and remove the packaging only before use

Before applying the adhesive tape, the surface must be clean and dry.
In case of particular processing it is advisable to evaluate the suitability of the product by means of a preliminary test.
Our technical staff is available for any support.
Prades Srl will not be responsible for any direct, indirect or incidental loss or damage resulting from incorrect use of the product. Therefore, the user assumes all risk and liability due to improper use of this article.

NOTE
The technical data shown in this sheet have been obtained from Prades Srl directly from the documentation provided by the manufacturer.
This data may be subject to change without prior notice.

PRADES SRL
Via 1° Maggio, 9
35035 Mestrino (PD) - ITALY

+39 049 9002797
web@prades.it
www.prades.it

Certificati ISO 9001