

PH400PETPR55RS

Support

Polyester (PET)
Clear

Adhesive

Rubber solvent base

Liner

Paper
White

Characteristics

Permanent removable double-sided tape, available in various formats. Open side: rubber solvent base adhesive; protected side: acrylic adhesive with good resistance to temperatures, plasticisers and UV rays. The PET support makes it dimensionally stable and suitable for punching. Product available in spools with extended liner.

Recommended for

Paper • Cardboard • Laminated cardboard • Polyethylene (PE) • Polypropylene (PPL)

Industries

Paper Mill • Paper products • Plastic Material

Applications

Bobbin start • Closing paper bags • Fastening credit cards on letters • Closing/opening plastic bags

Formats (mm x Mt)	Unit of Measurement	Carrier + adhesive thickness (my)	Peel Adhesion (N/25mm)	Min. working temperature (°C)	Max. working temperature (°C)
5/10x500; 6/12x500; 12/18x500	RT	55	5/30	+ 10	+ 50

TEST METHODS

International standards (FINAT, AFERA, PSTC, ASTM, TLMI, ISO).

SAFETY INFORMATION

This product is not classified as dangerous for the environment or human health and it complies with current regulations such as the REACH Regulation and the RoHS Directive.

USE AND STORAGE

The functionality and efficiency of the adhesive material is guaranteed 12 months from the date of delivery. We recommend to store it respecting the following indications:

- Environmental Temperature from + 15 ° C to + 22 ° C
- Humidity less than 65%
- Avoid exposing the material to direct light and sources of heat
- Store the material in the original packaging and remove the packaging only before use

Before applying the adhesive tape, the surface must be clean and dry.

In case of particular processing it is advisable to evaluate the suitability of the product by means of a preliminary test.

Our technical staff is available for any support.

Prades Srl will not be responsible for any direct, indirect or incidental loss or damage resulting from incorrect use of the product. Therefore, the user assumes all risk and liability due to improper use of this article.

NOTE

The technical data shown in this sheet have been obtained from Prades Srl directly from the documentation provided by the manufacturer.

This data may be subject to change without prior notice.




PRADES SRL
 Via 1° Maggio, 9
 35035 Mestrino (PD) - ITALY

 +39 049 9002797
 web@prades.it
 www.prades.it

Certificati ISO 9001



ISO 9001